



Model Number


V1S-G-OR15M-PUR-A

Single-ended male cordset, M12, 4-pin, PUR cable, welding-bead resistant

Features

- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching
- Gold plated contacts
- Halogen-free
- Suitable for drag chains
- Flame resistant cable
- Suitable for robotic applications / torsion resistant
- Improved resistance to weld slag

Dimensions



Technical data

General specifications

Number of pins	4
Connection 1	Male connector
Construction type 1	straight
Threading 1	M12
Connection 2	cable end

Electrical specifications

Operating voltage	U _B	max. 250 V AC/DC
Operating current	I _B	max. 4 A


Ambient conditions

Ambient temperature	Body: -40 ... 90 °C (-40 ... 194 °F) cable, fixed: -40 ... 80 °C (-40 ... 176 °F) cable, flexing: -25 ... 80 °C (-13 ... 176 °F)
Pollution degree	3

Mechanical specifications

Contact elements	spring-loaded contact socket
Pin diameter	1 mm
Degree of protection	IP67 / IP68 / IP69k
Cable code	LiF9Y11Y 4 x 0.34 mm ²
Material	
Contacts	CuSn / Au
Contact surface	Au
Body	TPU, black
Cable	PUR resistant to weld spatter
Sleeve connector	Diecast zinc
Core insulation	PP
Cable	extra-fine wire, flexible
Sheath diameter	Ø 4.3 mm
Bending radius	> 10 x cable diameter, moving > 5 x cable diameter, single bend
Color	orange
Number of cores	4
Core cross-section	0.34 mm ²
Conductor construction	42 x 0.1 mm Ø
Length	L 15 m
Drag chain suitability	
Drag chain cycles	≥ 5000000
Motion velocity	≤ 3.3 m/s
Traverse distance	5 m
Acceleration	≤ 5 m/s ²
Torsion cycles	≥ 1000000
Torsional stress	±180 °/m
Flammability	
Contact carrier	94 HB

Electrical connection



Release date: 2019-05-10 16:07 Date of issue: 2019-05-15 240771-100031_eng.xml



Housing	94 V-2
Cable	FT2
Compliance with standards and directives	
Standard conformity	
Degree of protection	EN 60529:2000
Standards	IEC 61076-2-101:2008
Flammability	Body: UL 94 Line: UL 1581 Section 1061; IEC 60332-1-2:2004
Halogen-free	IEC 60754-1:1994
Approvals and certificates	
UL approval	cURus AWM 20549 AWM I/II A/B 80°C 300V FT2

Accessories

- MH V1-SCREWDRIVER**
torque screwdriver (0.6 Nm)
- MH V1-BIT M12**
plug-in cap M12
- V1/V3-LABELHOLDER**
Label holder
- V1/V3-LABEL**
Label plate
- MH V1-Holder**
Modular universal holder for M12 connectors
- V1-CLIP**
Unlocking protector for M12 connector
- V1-MARKING-RING-BLUE**
Marking ring for M12 plug
- V1-MARKING-RING-GREEN**
Marking ring for M12 plug
- V1-MARKING-RING-ORANGE**
Marking ring for M12 plug
- V1-MARKING-RING-RED**
Marking ring for M12 plug
- V1-MARKING-RING-WHITE**
Marking ring for M12 plug
- V1-MARKING-RING-YELLOW**
Marking ring for M12 plug

Release date: 2019-05-10 16:07 Date of issue: 2019-05-15 240771-100031_eng.xml