



Model number

VAA-2E1A-PM-S

AS-Interface EMERGENCY STOP button

Features

- 2-channel, compelled connected
- Overload-protected in accordance with IEC 60947-5-5
- Integrated illumination in the actuator
- TÜV-approval for system components is available
- Biased actuator for self-monitoring
- EMERGENCY STOP unlocking by turning or pulling

Function


This AS-Interface emergency shutoff button is a two-channel, positively driven contact, allowing the operation of personnel protection systems when used according to specification along with an AS-Interface safety monitor. It occupies one complete address in the AS-Interface strand.

When the safety monitor is properly configured, up to EN 954-1 Category 4 and IEC 61508 SIL 3 can be achieved.


For mounting, this AS-Interface emergency shutoff button can be screwed into the front plate of the machine or the switch panel. The button can be illuminated in red.

A designation plate and suitable connection cable are included in the scope of delivery.

Dimensions



Electrical connection



Technical data

General specifications

Slave type	Safety-Slave
AS-Interface specification	V2.1
Required master specification	≥ V2.0
UL File Number	E198304

Functional safety related parameters

MTTF _d	200 a
B _{10d}	1 E+5

Electrical specifications

Rated operating voltage	U _e	26.5 ... 31.6 V from AS-Interface
Rated operating current	I _e	≤ 40 mA
Protection class		III
Insulation resistance		≥ 100 MΩ

Input

Number/Type	2 NC Safety function by positive opening in accordance with IEC/EN 60947-5-1 Reset by pulling
Supply	from AS-Interface

Output

Number/Type	LED red
Supply	from AS-Interface

Directive conformity

Electromagnetic compatibility	
Directive 2014/30/EU	EN 62026-2:2013

Standard conformity

Electromagnetic compatibility	EN 62026-2:2013
Degree of protection	EN 60529:2000
Electrical safety	EN 60947-5-5:1997+A1:2005
AS-Interface	EN 62026-2:2013
Functional safety	EN 62061:2005 EN 61508 Parts 1-7:2010 NFPA 79:2007 EN 60204-1:2006

Programming instructions

Profile	S-7.B.E.
IO code	7
ID code	B
ID1 code	F

ID2 code	E
Data bits (function via AS-Interface)	input output
D0	dyn. safety code 1 OUT 1
D1	dyn. safety code 1 -
D2	dyn. safety code 2 -
D3	dyn. safety code 2 -
Parameter bits (programmable via AS-i)	function
P0	not used
P1	not used
P2	not used
P3	not used
Ambient conditions	
Ambient temperature	-25 ... 55 °C (-13 ... 131 °F) (no freezing)
Storage temperature	-40 ... 70 °C (-40 ... 158 °F)
Relative humidity	40 ... 85 % , noncondensing
Mechanical specifications	
Operating force	Push: 32 N Pull: 21 N Turn: 0.27 Nm Minimum for positive opening operation: 60 Nm
Operating distance	for positive opening operation: min. 4 mm maximal: 4.5 mm
Degree of protection	IP65
Connection	Crimp terminal sockets (JST) 1.5 m Connecting cable with crimp on 2 flexible leads supplied with delivery
Installation	Installation in 22 mm hole
Mass	105 g
Life span	> 250,000 switching operations