

FT 25-W2-GS-M4

Ordering information

Designation for ordering	FT 25-W2-GS-M4
Part number	607-21014
Order text	White light contrast sensor, 12 +/- 2,5mm 10 kHz, Push Pull, teach in, plug M8 4-pins, IP67 & IP69K For this product a new version is available: 607-21034 FT 25-W2-GSL-M4 That offers additional functionality via IO-Link. More product information you can find on www.sensopart.com






Optical data	
Scanning distance [mm]	12
Scanning distance tolerance [mm]	-2.5 ... 2.5
Light source	LED
Light color	White
Light spot size [mm]	1 x 4
Switching frequency ≤ [Hz]	≤ 10,000
Explanation of switching frequency	f = 1 / (T x Nyq x 2)

Functions	
Display, LED yellow	Switching output indicator
Display, LED green	Operating voltage indicator
Setting options	LO / DO via the teach-in button and control input Button lock via control input
Sensitivity setting	Via teach-in button and control input
Teach-in modes	Mode 1: during running process Mode 2: when process at standstill

Electrical data	
Operating voltage UB [V DC]	10 ... 30
Explanation of operating voltage UB	max. 10% residual ripple, within UB, ~ 50 Hz 100 Hz
No-load current [mA]	≤ 30
Output current [mA]	≤ 100
Readiness delay [ms]	≤ 300
Reverse polarity protection	Yes
Short circuit protection	Yes
Response time Q [μs]	≤ 60
Control input	+UB = Teach-in - UB = button locked open = normal operation
Protection class	2
Jitter [μs]	25.0
Output function	LO/DO
Switching output Q	Push-pull
Number of outputs	1

Mechanical data	
Height [mm]	34.0
Length [mm]	20.0
Width [mm]	12.0
Weight [g]	~ 10
Front panel material	PMMA
Housing material	ABS
Ambient temperature: operation [°C]	-20 ... 55
Explanation of operation at ambient air temperature	UL: -20 +50
Ambient temperature: storage [°C]	-20 ... 80
Protection class	IP 67, IP 69
Explanation of protection class	With IP 67/ IP 69K plug connected
Vibration and shock resistance	EN 60947-5-2
Connection name	Plug M8, 4-pin

Technical drawings	
Dimensional drawing	 153-00995
Signal history	 155-01647
Connections	 154-00527

Product link

<https://www.sensopart.com/en/products/details/607-21014>